

SECTION 11110**TUMBLE DRYER, 75 LB. [34 KG] CAPACITY****PART 1 GENERAL****1.01 SECTION INCLUDES:**

- A. Automatic laundry dryer for processing water-washed linen items

1.02 SYSTEM DESCRIPTION**A. DESIGN REQUIREMENTS:**

1. Dry weight capacity: lb. 75 [34]
[kg]
2. Cylinder volume: 22.4 [634] minimum
feet³ [Liter]
3. Construction: Heavy duty embossed steel with e-coat and baked enamel
powder paint
4. Input voltage: G: 230-240/50-60/3
L: 460-480/50-60/3
5. Heat source, kW: Electric, 36
6. Overall width: in. [mm] 38.5 [980] nominal
7. Overall height: in. [mm] 77.3 [1960] nominal
8. Overall depth: in. [mm] 53.0 [1350] nominal
9. Exhaust size: Inch [mm] 8.0 [200]
10. Control system: Microprocessor touchpad control
11. Stainless steel door: High grade stainless steel door with 7/8 in. [22 mm] rubber
gasket and two point heavy duty hinge

B. PERFORMANCE REQUIREMENTS:

1. Airflow: C.F.M. [l/sec] 800 [380]
2. Drive Motor: Horsepower 0.5 [0.4]
[kW]
Fan Motor: Horsepower 0.5 [0.4]
[kW]
3. Control system
 - a. Programming methods: Machine keypad, Infrared (PC or PDA)
 - b. 30-Cycle Capability
 - c. PC software to program machine and/or audit machine performance
 - d. Record last eight machine errors by date and time
 - e. OPTIONAL Over Dry Prevention Technology (OPTidry[™]) System utilizes two cylinder lifters as sensors; Maintenance-free rotary transfer switch communicates signal between OPTidry[™] sensor/lifters and control
 - f. Wrinkle free at cycle end allowing 30 seconds of tumble and 1-1/2 minutes of rest until door opens or maximum of one hour
4. Lint filter: 576 sq. in. [3716 sq. cm] , self cleaning, depositing lint to large
storage area at bottom of tumble dryer

- 5. Cylinder Type (position 10 of model number) Nonreversing - N digit
 Reversing (optional feature) - R digit

1.03 DELIVERY, STORAGE AND HANDLING

A. ACCEPTANCE AT SITE:

- 1. Inspect machine for damage prior to acceptance. If damage is found, follow freight handler's procedure for claims.

B. STORAGE AND PROTECTION

- 1. Machine should be stored in a site protected from weather, direct sunlight and temperature extremes. Do not remove packaging prior to storage.
- 2. If machine is to be stored for an extended period of time, consult manufacturer for special requirements.

1.04 WARRANTY

- A. Warranty Period: Three years, limited, parts only, commencing on Date of Substantial completion

1.05 SYSTEM STARTUP AND COMMISSIONING

- A. Machine installation should be inspected by local manufacturer's representative prior to startup and operation. The party installing the machine is responsible for setting the schedule for this inspection.

PART 2 PRODUCTS

2.01 MANUFACTURERS

- A. Alliance Laundry Systems LLC - UniMac, obtain commercial laundry equipment from a single manufacturer

2.02 QUALIFIED MODELS

- A. UniMac model **UT075ENN** (no substitutions permitted)

PART 3 EXECUTION

3.01 INSTALLATION

- A. Refer to and comply with manufacturer's installation instructions. Do not deviate without permission from site owner, architect, general contractor and manufacturer's local representative.

Machine Dimensions and Specifications


Model UT075E



Equipment specifications are subject to change without notice.

Design 6

Machine Dimensions and Specifications



Dimensions

A	29.2 [740]	I	38.5 [980]
B	33.9 [860]	J	8.0 [200]
C	53.0 [1350]	K	5.8 [145]
D	35.5 [900]	L	6.0 [150]
E	39.2 [1000]	M	33.0 [840]
F	13.8 [350]	N	36 [910]
G	V-Control: 76.5 [1945] All Other Controls: 77.3 [1960]		
H	14.0 [355]		
in. [mm]			

Specifications

Net Weight (approximate): Pounds [kg]	730 [330]
Required Make-Up Air Opening (to the outside) for Each Tumble Dryer, in. ² [cm ²]	195 [1,260]
Maximum Airflow: C.F.M. [l/sec]	800 [380]
Maximum Static Back Pressure: Inch W.C. [mbar, kPa]	V-Control: 0.52 [1.3, 0.13] All Other Controls: 0.50 [1.2, 0.12]
Heating Element Rating: Kilowatts	36

Electrical Specifications

Voltage Code	Voltage	Cycle	Phase	Wire	Full Load Amps	Circuit Breaker	Wire Size AWG [mm ²]
G	230-240	50-60	3	L1, L2, L3 and ground	90	125	1 [35]
L	460-480	50-60	3	L1, L2, L3 and ground	45	60	6 [16]